

Proposal By: Westboro Tennis
Surfaces

To:

For: Stone Dust, Fast Dry
New Construction

We will perform the following work and provide the materials indicated:

1. The site will be surveyed to establish proper grades and to assure drainage.
2. The existing topsoil will be excavated and spread around the perimeter of the court.
3. Four inches or 150 tons of processed gravel, will be spread, graded with a laser guided grader and compacted with a power roller to a slope of 1" in 20' according to USTA specifications so as not to vary more than 1/4" in 10' when measured in any direction.
4. At this stage, all fence post and net post foundations shall be dug, poured and set in concrete with sleeves. This is to insure that there are no shrinkage cracks between the asphalt surface and the concrete fence and net post foundations that occur when the fencing is installed following the paving. The fence post foundations shall be twelve inches by twelve inches (12"x12") at the top and measuring three feet (3') deep. The net post holes will measure two feet by two feet (2' x 2') at the top, three feet (3') deep and bell out to thirty-six inches (36") at the bottom to prevent heaving. The center anchor shall be set in concrete measuring twelve inches by twelve inches by twelve inches (12"x12"x12"). All fence posts shall be black vinyl coated, terminal and corner fence posts shall be 2.875" O.D. Line posts shall be 2.375" O.D. It must be noted that paving shall be continuous in that each pass must be completed in order to eliminate the occurrence of cold joints.
5. A leveling course consisting of two inches (2") of Stone Dust will be applied and graded with a laser guided grader according to USTA specifications so as not to vary more than 1/8" in 10' when measured in any direction.
6. At this point, the remaining fence frame work consisting of one and five eighth inch (1 5/8") top rail, corner and terminal braces shall be installed. Also to be installed is a bottom wire around the entire perimeter of the court. The entire fence area shall be ten feet (10') high. From the 10' framework nine (9) gauge one and three quarter inch (1 3/4") black vinyl coated fabric shall be hung. The fence shall measure three hundred feet (300').
7. The leveling course will be covered by 1" of Fast Dry after compaction. It will

then be laser graded and rolled thoroughly.

8. A paver brick edging will be installed around the perimeter of the court.

9. The playing area will be marked by 2" tapes and secured by aluminum nails. A set of internal wind net posts in sleeves shall be installed which will be removable for winter storage. A Court Master DHS net with center strap and anchor will be hung. Also included are a drag broom and a line sweeper.

10. An automatic sprinkler system will be installed consisting of six (6) Hunter Pop-up Sprinkler Heads and a six station automatic timer. It is the owner's responsibility to furnish a 1" line to the exterior of the house with a minimum of 50 lbs. of pressure.

The cost for the above _____ \$

We have included in this proposal the use of an excavator for 3 days, a bulldozer for 5 days, a vibratory roller for 4 days. Should the desired result be achieved in less than 5 days, the owner will receive a credit for the appropriate machine time.

Not included in the above price are any ledge or rock problems or conditions requiring blasting or, the removal of any boulders 1 cubic yd. or larger as well as any additional fill required as a result of the rock problem.

Should the site require additional machine time or more gravel, the cost would be based on the following:

Should additional bulldozer subgrade work be required, per 9 hour day at \$75.00/hr., the cost would be _____ \$675.00/day

Should additional vibratory roller work be required, per 9 hour day at \$55.00/hr., the cost would be _____ \$495.00/day

Should additional excavator work be required, per 9 hour day at \$85.00/hr., the cost would be _____ \$765.00/day

Should additional rubber-tired backhoe be required, per 9 hour day at \$75.00/hr., the cost would be _____ \$675.00

Should any conditions warrant more gravel, the cost would be \$7.50 per yard, plus tax, spread and compacted in place.

Should an interceptor drain be needed consisting of 3/4" washed stone and 4" perforated pipe, the cost would be \$14.00 per foot.

Should any material need to be removed from the site, the cost would be billed at \$50.00 an hour per truck.

If stumps require removal from the site, there will be an additional charge.

Not included in the above price are any ledge or rock problems or conditions requiring blasting or, the removal of any boulders 1 cubic yd. or larger as well as any additional fill required as a result of the rock problem.

OWNER SHALL BE RESPONSIBLE FOR ANY PERMITS REQUIRED.